# CARMINAWOOD

## DOWNSTREAM SANITARY SEWER CAPACITY ANALYSIS REPORT

for

### **Multi-Family Project**

0, 46-84 South Linden Street Town of Amherst, Erie County, New York

Prepared for

South Linden, LLC

493 Kennedy Road Cheektowaga, NY 14227

Prepared by

**Carmina Wood Design** 

80 Silo City Row, Suite 100 Buffalo, NY 14203

Telephone: (716) 842-3165 Fax: (716) 842-0263

> November 2025 Rev. December 2025



#### **Project Description**

This project is a development of a 2.4 acre site located of the vacant land on South Linden Street in the Town of Amherst. Construction will consist of two multi-family buildings totaling 28 units, with detached garage buildings, associated utility, lighting and landscaping improvements. Currently the site is undeveloped consisting of mostly wooded areas. The proposed site development area to be disturbed for this project is approximately 2.25 acres when construction is completed.

Proposed is approximately 335 If of 6" SDR-35 PVC private sanitary sewer, connected to the existing public sanitary sewer main along the north side of McIntire Road. Each proposed building will wye connect to the proposed 6" sanitary lateral via 6" SDR-35 PVC sanitary laterals at 1.0% minimum slope. Wastewater from the proposed development will flow north under the thruway then north along Long Street, west along Reist Street, and north along North Forest Road, then west along Sheridan Drive through the Town's West Side Interceptor sewer (54"). Flow then goes west and north until ultimately reaching the Town of Amherst Wastewater Treatment Facility (60" to 84"). Refer to the sewer interceptor map located in the TECSmith monitoring section of the downstream sewer capacity analysis report.

#### Node 1 - Garden Parkway (12"):

Existing Peak Flow measured (wet weather event) = 1.675 cfs (1.083 mgd)\*
Proposed Multi-Family Peak Flow = 0.035 cfs\*\*

Proposed Total Peak Flow = 1.710 cfs

Theoretical capacity of existing 12" VTP pipe @ 0.22% = 1.550 cfs

<u>Conclusion:</u> Monitored flows the day of a 1.81" rainfall event exceeded the theoretical capacity of the existing pipe 12" sewer. However, at no time during the monitoring did the flow depth exceed the pipe diameter at Node 1 did flow slow or stall which would have caused a backup or flooding at the manhole. In addition, Sanitary Sewer Overflow (SSO) did not occur. I/I mitigation shall be required for the contribution of this proposed project, and should occur prior to and/or simultaneously as the project implementation in order to ensure adequate capacity exists, and the risk for an SSO is limited.

#### Node 2 - 224 N Long Street (18"):

Existing Peak Flow measured (wet weather event) = 6.080 cfs (3.930 mgd)\*

Proposed Multi-Family Peak Flow = 0.035 cfs\*\*
Proposed Total Peak Flow = 6.115 cfs

Theoretical capacity of existing 18" VTP pipe @ 0.10% = 3.082 cfs

<u>Conclusion:</u> Monitored flows the day of a 1.81" rainfall event exceeded the theoretical capacity of the existing pipe 18" sewer. However, at no time during the monitoring did the flow depth exceed the pipe diameter at Node 1 did flow slow or stall which would have caused a backup or flooding at the manhole. In addition, Sanitary Sewer Overflow (SSO) did not occur. I/I mitigation shall be required for the contribution of this proposed project, and should occur prior to and/or simultaneously as the project implementation in order to ensure adequate capacity exists, and the risk for an SSO is limited.

### Node 3 - West Side Interceptor (54"):

Existing Peak Flow measured (wet weather event) = 14.774 cfs (9.55 mgd)\*
Proposed Multi-Family Peak Flow = 0.035 cfs\*\*
Proposed Total Peak Flow = 14.809 cfs


Capacity of existing 54" West Side Interceptor sewer = 56.466 cfs (36.5 mgd)

<u>Conclusion:</u> The proposed total peak flow is less than the capacity of the 60" Peanut Line sewer, therefore there is sufficient capacity.

### Foot Notes:

Downstream capacity node information provided by Town of Amherst Engineering Department \*Converted from measurements in TECSmith report dated 11/11/25
\*\*See Sanitary Sewage Demand Calculations

### **Location Map**



### **Sanitary Demand Calculations**

**CARMINA WOOD DESIGN** 

80 SILO CITY, SUITE 100 BUFFALO, NEW YORK, 14203 (716) 842-3165

FAX (716) 842-0263

Project No.: 23-4154 Date: 9/22/2025

Project Name: Multi-Family Development rev. 12/15/2025
Project Address: S Linden Street Amherst, NY

Subject: Sanitary Sewer & Water Demand Calcs

Sheet: 1 of 2

													- 8	-		8			
110 gal/d/unit	X		units		1,320	gpd							er u						
220 gal/d/unit	X		units		2,640	gpd							er u						
330 gal/d/unit	X	4 ւ	units	=	1,320	gpd		*	use 3	30	gallo	ns p	er u	nit <sub>l</sub>	oer	day	(3-	bdrn	n
						h													1111
																ļ			
																ļ			
Total Site Sanitary Demand:				=	<u>5,280</u>	gpd										ļ			
ind Peak Sanitary Demand:																			
Doubier France Level III		<u>.</u>														Ē			1111
Peaking Factor based on P Total demand:	opulation 5,280			100	gpcd	=	53 pe	rcan	it a										
Total demand.	3,200	gpu		100	gpcu		33 be	п сар	ııa										
	Pop	ulati	on (P)	· =		53 pe	ople												
Peaking Factor: (18	8 +√P) / (·	4 + √	P)	w	here P is ir	thous	ands												
	1 24	ļ				ļ										ļ	ļ		
Peaking Factor =	4.31															ļ			
Peak Sanitary Demand	=	5.2	80 x	4.31	=	22,756	gnd									ļ			
					=	0.023										ļ	j		
					=	0.035											Ö		1111
		)																	2111
<u>equired Infiltration and Inflow</u>	<u>Mitigation Mitigation Mitigation</u>	<u>on:</u>														ļ			
					22,756	and	=	15.9	30 gp	m									
Pook Spritary Flow		1						13.0	ou gp			- 8							
Peak Sanitary Flow				=	22,730	gpu				· · · ·						Ē			
	:quiremer	ıts		=		gра х 4					eq'd					ā Ē B	ā ā		
Peak Sanitary Flow 4:1 offset flow per NYSDEC re	equiremer:	nts							21 gp		eq'd								
	:quiremer	nts				x 4	=				eq'd								
4:1 offset flow per NYSDEC re Mitigation Credit		nts			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re		nts		=	15.80 \$250	x 4					eq'd								
4:1 offset flow per NYSDEC re Mitigation Credit		nts			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re Mitigation Credit		ıts			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re Mitigation Credit		nts			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re		nts			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re		its			15.80 \$250	x 4 / gpm					eq'd								
4:1 offset flow per NYSDEC re		nts			15.80 \$250	x 4 / gpm													
4:1 offset flow per NYSDEC re		nts			15.80 \$250	x 4 / gpm													
4:1 offset flow per NYSDEC re		nts			15.80 \$250	x 4 / gpm													
4:1 offset flow per NYSDEC re		nts			15.80 \$250	x 4 / gpm													
4:1 offset flow per NYSDEC re Mitigation Credit		nts			15.80 \$250	x 4 / gpm													
4:1 offset flow per NYSDEC re Mitigation Credit		nts			15.80 \$250	x 4 / gpm													

### **TECSmith Monitoring Report**

### **TECsmith**

TECSMITH, Inc. PO Box 95 Clarence, NY 14031 716-462-0382

Date: November 11, 2025

#### SANITARY SEWER FLOW CAPACITY STUDY – Summary Review

**Prepared For:** South Linden - Downstream Monitoring Capacity Analysis.

Chris Wood Carmina Wood Design 80 Silo City Row Buffalo, New York 14203

Project Name: South Linden - Downstream Monitoring Capacity Analysis.

Flow Monitoring Period: October 8, 2025, to November 5, 2025

**Rain Events (> 0.5-inches) Monitored:** October 19 (0.53), October 22 (1.81"), and October 30 (0.58")

Number of Monitoring Nodes: Two (2) downstream manholes

### **Node Locations and Descriptions:**

Node 1 Garden Parkway (12")Node 2 224 North Long Street (18")

### **Summary Conclusion:**

Based on the data presented in this report, specifically the flow depth measurements recorded (see graphs below)


- At no time did the flow depth exceed pipe diameter at any of the downstream monitoring points during the wet weather vents monitored.
- At no time during the monitoring period did the flow at any point slow or stall which would have caused a backup or flooding at the manhole.

TECSMITH, Inc. PO Box 95 Clarence, NY 14031 716-462-0382

### **Depth of Flow Capacity Summary:**


Depth of flow capacity is based on diameter of pipe. See graphs below.

• At no time during the monitoring period did depth of flow exceed pipe diameter at Node 1.



TECSMITH, Inc. PO Box 95 Clarence, NY 14031 716-462-0382

• At no time during the monitoring period did depth of flow exceed pipe diameter at Node 2.



4.71	:		1	-	1		1	ı	!
0.11	2.240	4.158	0.339	23.151	5.600	1.176	0.273	40.298	11/5/2025
0	3.840	4.756	0.747	346.374	5.900	1.178	0.279	123.773	11/4/2025
0.11	1.660	4.173	0.214	6.290	6.490	1.157	0.293	114.708	11/3/2025
0	3.760	4.516	0.761	244.576	5.880	1.030	0.223	79.170	11/2/2025
0	4.080	4.557	0.838	564.455	5.660	1.110	0.243	123.063	11/1/2025
0.08	4.490	4.724	0.993	712.735	6.820	1.216	0.281	124.930	10/31/2025
0.58	5.530	5.434	1.584	463.663	8.350	1.600	0.587	195.161	10/30/2025
0	3.210	4.401	0.595	339.315	5.640	1.451	0.291	105.942	10/29/2025
0	3.980	4.413	0.767	426.896	5.620	1.137	0.218	96.931	10/28/2025
0	3.940	4.467	0.734	466.145	5.490	1.369	0.268	100.560	10/27/2025
0	4.000	4.529	0.756	506.091	5.590	1.115	0.247	95.929	10/26/2025
0.01	4.340	4.423	0.862	654.687	5.410	1.121	0.227	101.755	10/25/2025
0	4.640	4.743	1.008	800.895	5.470	1.293	0.291	139.638	10/24/2025
0.13	6.420	5.814	2.125	1036.431	7.660	1.702	0.378	182.984	10/23/2025
1.81	10.640	5.931	3.930	2188.124	11.050	2.216	1.083	528.442	10/22/2025
0.29	5.980	4.734	1.570	635.355	7.040	1.414	0.438	146.612	10/21/2025
0.38	6.230	5.628	1.914	917.727	8.740	1.657	0.645	206.121	10/20/2025
0.53	6.200	5.463	1.817	644.350	8.750	1.642	0.650	215.276	10/19/2025
0.24	4.090	5.463	0.798	488.510	6.830	1.446	0.408	145.204	10/18/2025
0	3.590	4.291	0.625	397.751	5.620	1.658	0.245	113.700	10/17/2025
0	3.610	4.017	0.671	419.202	5.830	1.202	0.276	104.297	10/16/2025
0	3.680	4.277	0.719	429.175	5.600	1.279	0.271	132.427	10/15/2025
0	3.480	4.284	0.641	442.953	5.670	1.163	0.257	128.719	10/14/2025
0	3.640	4.190	0.639	449.144	5.700	1.408	0.307	139.641	10/13/2025
0	3.730	4.248	0.676	459.709	5.920	1.589	0.360	131.728	10/12/2025
0.39	4.340	4.435	0.890	491.420	6.580	1.722	0.312	141.519	10/11/2025
0	3.740	4.235	0.723	447.470	5.770	1.672	0.330	123.079	10/10/2025
0	4.010	4.240	0.778	500.304	5.790	1.102	0.255	80.179	10/9/2025
0.05	3.780	4.355	0.676	191.020	030.9	1.146	0.272	141.938	10/8/2025
	LEVEL (IN)	(FPS)	(MGD)	(GAL x 1,000)	LEVEL (IN)	(FPS)	(MGD)	(GAL x 1,000)	
(inches)	PEAK	PEAK VEL.	PEAK FLOW	FLOW	PEAK	PEAK VEL.	PEAK FLOW	FLOW	
		g (18")	224 N Long			kway (12")	Garden Parkway (12")		
Rain		2	Node 2			e 1	Node 1		Date

**Town of Amherst Sanitary Sewer Downstream Routing Maps** 

